



# GG010Y

## ARTICULATED LOADER

With a rated load capacity of 1000 kg and a 0.5 m<sup>3</sup> bucket, the GG010Y easily handles loading and transporting a wide range of materials. A maximum breakout force of 28 kN ensures efficient operation even in the toughest terrain.

Powered by the proven Yunnei DEF20CHF4 engine with 25 KM and four cylinders, operating at 2400 rpm, the GG010Y delivers consistent performance. The fully hydraulic steering system and four-wheel drive ensure smooth and confident handling in any environment. With an overall length of 4100 mm, width of 1600 mm, and height of 2530 mm, the GG010Y is ideal for spaces with limited room. A minimum turning radius of 4600 mm allows for precise maneuvering even in tight areas. The loader is equipped with a four-wheel hydraulic braking system and a manually operated parking brake for enhanced safety.

### ■ Specification

Operating Weight	3500 kg
Rated Load Capacity	1000 kg
Bucket Capacity	0,5 m <sup>3</sup>
Engine Brand	Yunnei
Engine Model	DEF20CHF4
Rated Power	25 KM
Rated Speed	2400 rpm
Number of Cylinders	4
Steering System	Fully hydraulic
System Pressure	10 Mpa
Tires	10-16,5
Parking Brake	Manually operated
Service Brake	Four-wheel hydraulic brake


### ■ Working Range

Bucket Width	1600 mm
Drive Type	Four-wheel drive
Dumping Height	2560 mm
Wheelbase	2170 mm
Maximum Breakout Force	28 KN
Minimum Turning Radius	4600 mm
Track Width	1285 mm

### ■ Dimensions

Overall Length (bucket on the ground)	4100 mm
Overall Height	2530 mm
Overall Width	1600 mm

### ■ Additional equipment (for reference)



4-in-1 Bucket



Grapple (Crocodile-type)



Pallet Forks



Auger



Bale Grab



Sweeper



Mower



Snow Plow



Bucket with grapple

