



# CFPT0608SP

## ELECTRIC SCISSOR LIFT

One of the key advantages of this model is its maximum working height of 7.8 meters which allows easy access to hard-to-reach areas. Despite its impressive performance, the platform offers an excellent load capacity of 230 kg, creating opportunities for a variety of applications, and at full extension, the load capacity is 113 kg. This makes the CFPT 0608SP – 6M perfect for both narrow spaces and large construction sites.

Thanks to its efficient 3.3 kW electric motor, the lift combines environmental friendliness with excellent performance. The electric drive makes it practically silent during operation and emits no exhaust gases, making it ideal for use in enclosed spaces and facilities where environmental standards are especially important. Additionally, the optimal lifting speed of 18 mm/s and lowering speed of 22 mm/s ensure precise control over the platform's movement.

### ■ Specification

Weight	1540 kg
Lifting Motor	3.3 Kw
Battery	24 V 200 Ah
Battery Charger	24 V 25A
Wheels	305*100mm
Max. Working Height	780 cm
Max. Platform Height	580 cm

### ■ Working Range

Travel speed (retracted)	3.5 km
Lifting speed	18 mm/sec
Climbing ability	25 %
Travel speed (elevated)	0,8 km/h
Lowering speed	22 mm/sec
Max. Working Slope	1.5 - 3

### ■ Dimensions

Length (L)	1860 mm
Width (W)	790 mm
Height (handrails up)	2180 mm
Height (handrails down)	1795 mm
Platform dimensions	1670*755
Wheelbase	1085 mm
Ground clearance	86 mm

