



GG04

MINI LOADER

The vehicle is equipped with a bucket with a capacity of 0.15 m³ and a load capacity of 400 kg. Thanks to this, the GG04 is an ideal solution for loading and unloading materials in various industries, such as construction or agriculture. The bucket enables easy handling even in narrow and hard-to-reach areas.

The loader is equipped with a Briggs & Stratton engine featuring two cylinders and air cooling. This type of engine ensures reliability and high power, while the air cooling system makes the engine resistant to overheating, which is crucial during prolonged operation in varying weather conditions. Gasoline-powered, the loader is ready to work in all environments.

Specification

| | |
|---|---------------------|
| Machine Weight | 800 kg |
| Number of Cylinders | 2 |
| Drive | Gasoline |
| Minimum Height | 1270 mm |
| Bucket Load Capacity | 400 kg |
| Hydraulic Pump | Parker |
| Engine Displacement for Walking Mechanism | BM5-375 ml |
| Rated Power | 17 kw |
| Tire Specifications | 18*8.50-8 |
| Fuel Tank Capacity | 20 L |
| Engine Model | Briggs Stratton |
| Cooling Method | Air-cooled |
| Maximum Height | 2400 mm |
| Bucket Capacity | 0.15 m ³ |
| Nominal Pressure | 18 Mpa |
| Hydraulic Pump Flow Rate (L/min) | 15+15+15 l/min |
| Distributor | Italy M45 |
| Engine Oil Capacity | 1.7 L |
| Hydraulic Oil Tank Capacity | 25 L |

Main Dimensions

| | |
|-----------------------------|---------|
| Length | 2230 mm |
| Height | 1300 mm |
| Width | 1150 mm |
| Wheelbase | 640 mm |
| Bucket Width | 1150 mm |
| Maximum Slope for Operation | 25% |
| Ground Clearance | 100 mm |

Operating Range

| | |
|--------------------------|--------------|
| Maximum Loading Height | 2080 (mm) |
| Rated Speed | 3200 (r/min) |
| Maximum Unloading Height | 1950 (mm) |

Additional equipment

| |
|-----------------|
| Forks bucket |
| Grab bucket |
| 4-in-1 bucket |
| Chain trencher |
| Snow plow |
| Pallet fork |
| Grading scraper |



