



3T 3M ROTATOR DIESEL

Starting with the basics, this forklift is powered by a XINCHAI EURO 5 diesel engine, providing substantial power and ensuring compliance with environmental protection standards. The engine with a power of 44.8 kW and 2400 rpm enables the device to reach speeds of up to 18/19 km/h, which is extremely useful in dynamically changing warehouse or construction site conditions. With a load capacity of up to 3000 kg and a lifting height of up to 3 meters, it makes it an ideal solution for intensive use.

This forklift features massiveness and stability thanks to its weight of 4270 kg, allowing safe lifting and transportation of heavy loads. The rotator, incorporated into the design, gives the operator the ability to easily and precisely maneuver, and combined with a minimum turning radius of 2400 mm, significantly facilitates movement in tight spaces. Additionally, the integrated side shift forks support the seamless handling of various types of loads, enhancing the functionality and versatility of the device.

■ Specification

| | |
|---------------------|-----------------|
| Rotator | Yes |
| Side Fork Shift | Integrated |
| Load Capacity | 3000 kg |
| Tire Type | Pneumatic |
| Brake | Hydraulic Pedal |
| Engine | XINCHAI EURO 5 |
| Engine Power | 44.8 KW |
| Fuel Tank Capacity | 60 L |
| Weight | 4270 kg |
| Drive | diesel |
| Mast | duplex |
| Transmission | Automatic |
| Battery | 12V 80Ah |
| Number of Cylinders | 3 |
| RPM | 2400 |

■ Operational Range

| | |
|---------------------|--------------|
| Travel speed | 18/19 km/h |
| Max. Towing Force | 20/156 KN |
| Speed with Load | 440/480 mm/s |
| Min. Turning Radius | 2400 mm |

■ Dimensions

| | |
|-----------|--------------------------|
| Length | 2900 mm |
| Height | 2090 mm |
| Width | 1230 mm |
| Fork Size | 1200 mm x 120 mm x 40 mm |

