



## CDD10EL

### ELECTRIC LIFT

With a load capacity of up to 1000 kg and a maximum lifting height of 3 meters, this stacker offers remarkable versatility in lifting and transporting goods. Even at full height, it can lift loads weighing up to 700 kg, making it an ideal solution for use in confined spaces.

At its core, the stacker features powerful motors: a 2.2 kW lifting motor and a 0.75 kW drive motor. These allow the machine to achieve impressive performance, with lifting speeds of up to 136 mm/s and lowering speeds of up to 112 mm/s. Power is provided by a 24V 100Ah AC battery, offering up to 3 hours of continuous operation on a full charge. A modern 24V 90A controller and 24V 10A charger ensure smooth and safe operation. The CDD10 EL - 1T is a machine that not only meets performance expectations but also reflects the manufacturer's attention to detail, offering top-level reliability.

#### ■ Specification

|                    |                       |
|--------------------|-----------------------|
| Model              | CDD10 EL - 1T         |
| Battery Type       | AC                    |
| Battery Voltage    | 24V 100Ah             |
| Battery Dimensions | 260mm x 169mm x 215mm |
| Controller         | 24V 90A               |
| Charger            | 24V 10A               |
| Lifting Motor      | 2.2 kW                |
| Drive Motor        | 0.75 kW               |
| Weight             | 465 kg                |

#### ■ Operating Parameters

|                               |               |
|-------------------------------|---------------|
| Turning Radius                | 1336 mm       |
| Lowering Speed                | 112 / 98 mm/s |
| Driving Speed (Unloaded)      | 4.2 km/h      |
| Lifting Speed                 | 92 / 136 mm/s |
| Driving Speed (Loaded)        | 4 km/h        |
| Operating Time on Full Charge | 3 h           |

#### ■ Dimensions

|                      |         |
|----------------------|---------|
| Fork Length          | 1150 mm |
| Total Fork Width     | 1755 mm |
| Load Center Distance | 600 mm  |
| Min Mast Height      | 1994 mm |
| Single Fork Width    | 160 mm  |
| Total Width          | 795 mm  |
| Max Mast Height      | 3424 mm |

