



GG090

ARTICULATED LOADER

The machine offers a 900 kg load capacity and is equipped with a 0.5 m³ bucket with a width of 1650 mm, enabling convenient loading and transportation of bulk materials. A lifting height of 2750 mm and a maximum lifting height of 3110 mm allow efficient handling of transport vehicles and material stacking.

The loader is powered by a four-cylinder Kubota V1505 diesel engine compliant with the Euro 5 emission standard. A rated power of 24.47 HP at 2400 rpm, combined with an oil flow of 35 l/min, ensures stable and reliable performance during daily operations.

A travel speed of up to 12 km/h allows efficient movement across the worksite, while the operating weight of 2300 kg provides adequate stability when working with loads.

■ Parameters

Model	GG090
Engine	Kubota Euro 5 (V1505)
Rated engine power	24.47 KM
Number of Cylinders	4
Nominal Speed	2400 r/min
Machine Weight	2300 kg

■ Dimensions

Length with bucket lowered	4067 mm
Overall height	2410 mm
Overall width	1451 mm

■ Scope of work

Travel Speed	12 km/h
Bucket Capacity	0.5 m ³
Bucket width	1650 mm
Wheelbase (distance between axles)	1595 mm
Lifting height	2750 mm
Maximum lifting height	3110 mm
Rear overhang	1123 mm
Dump reach at full height	603 mm
Ground clearance	351 mm

